
BIG SKY TOWER 60D - 5FT X 12FT (NON-BACKLIT)

PRODUCT CODE: BIGSKYT60D5X12-FRM







PRODUCT DESCRIPTION

The Big Sky Tower is part of the Resort Extrusion family—aluminum frames for Silicone-Edge Graphics (SEG). Custom-made on the premises, Big Sky Tower comes in varied sizes. Big Sky Tower accepts four individual custom fabric graphics, excluding top and bottom. Insert graphics after frame is constructed by tilting it on its side. Transversely, push corners of graphic into the frame's recessed groove. Then, starting midway on the frame going toward the corners, continue pushing in the straight edges of the graphic. Repeat three times. Backlit option is available.

DISPLAY DIMENSION	5" L x 5" W x 12" H
-------------------	---------------------

GRAPHIC DIMENSIONS 60" W × 144" H

GRAPHIC MATERIAL

Stretch Fabric

GRAPHIC FINISHING

Silicone beading is sewn around the perimeter of the fabric graphic. Silicone beading is hidden from view once installed.

DISPLAY CONSTRUCTION

Aluminum Extrusion Frame


SHIPPING WEIGHTS & DIMENSIONS

Shipping Weight	77 lbs (frame only) 85 lbs (with graphics)
Shipping Dimensions	48" H x 18" W x 11.5" D

GRAPHIC TURN AROUND TIME

2 business days after proof approval

AVAILABILITY CA



Top View



Corner View

BIG SKY TOWER 60D - 5FT X 12FT (NON-BACKLIT)


PRODUCT CODE: BIGSKYT60D5X12-FRM




PRODUCT CODE: BIGSKYT60D5X12-FRM

SET UP INSTRUCTIONS 1/2


1. Attach Split Connectors to Side Extrusions:



a. Remove the screw and insert split connector into one end of the extrusion. Match like colored numbers together. (e.g. 3-3, 4-4).



b. Tighten screw to lock it into place. Remove the remaining screw from the connector.



c. Then slide the other extrusion onto split connector. Make sure extrusions are flush and tighten the screw to secure connection.

2. Locate the Bottom and Side Extrusions:



a. See colored numbers on each extrusion piece. Match like colored numbers together. (e.g. 3-3, 4-4).



b. End Lock is already attached to opposite ends of extrusion.



c. Connect horizontal extrusion to the bottom of a vertical extrusion, screw facing inward.



d. Connect bottom extrusions together and use torx key to tighten.

3. Locate the Top and Side Extrusions:



a. See colored numbers on each extrusion piece. Match like colored numbers together. (e.g. 3-3, 4-4).



b. End Lock is already attached to opposite ends of extrusion.



c. Connect horizontal extrusion to the top of a vertical extrusion, screw facing inward.




d. Connect the top extrusions together and use torx key to tighten.


4. Build Support Struts:



a. Remove screws from Center Connector.



b. Insert Center Connector and align holes with holes on extrusion.



c. Repeat to connect other extrusion to make one long piece.


PRODUCT CODE: BIGSKYT60D5X12-FRM

SET UP INSTRUCTIONS 2/2

5. Attach Support Strut to Frame:



a. End Lock is already attached to opposite ends of Support Strut.



b. Align Support Struts within marked lines, and insert End Lock into top and bottom grooves of frame.



c. Add a second support strut to align marked lines and tighten screws with torx key to secure connection.