37.75″ height

BS
OR-G-CA3-A

bleed area
trim line

BS
OR-G-CA3-B

BS
OR-G-CA3-C

BS
OR-G-CA3-D

gray area will
be obstructed
once finished
and mounted

38.125″ width

43″ width

Canis
20' x 20' Truss System
Dye Sub Printed

TEMPLATE IS @ 1/2 SCALE
Panels CA1-A, CA1-B, CA1-C, CA1-D:
Total Graphic Area: 42.125"w x 87.75"h
Finished Size: 38.125"w x 83.75"h

Panels CA2-A, CA2-B, CA2-C, CA2-D:
Total Graphic Area: 47"w x 87.75"h
Finished Size: 43"w x 83.75"h

Panels CA3-A, CA3-B, CA3-C, CA3-D:
Total Graphic Area: 78.75"w x 41.75"h
Finished Size: 74.75"w x 37.75"h

Panels CA4-A, CA4-B, CA4-C, CA4-D:
Total Graphic Area: 42.125"w x 87.75"h
Finished Size: 38.125"w x 83.75"h

Panels CA5-A, CA5-B, CA5-C, CA5-D:
Total Graphic Area: 47"w x 87.75"h
Finished Size: 43"w x 83.75"h

Template requires 1" bleed around the perimeter (2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4"w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

FS
OR-G-CA1-A

bleed area
trim line

FS
OR-G-CA2-A
panel is notched
on top
right side.

FS
OR-G-CA4-A
panel is notched
on top
left side.

FS
OR-G-CA5-A

FS
OR-G-CA1-B

FS
OR-G-CA2-B
panel is notched
on top
right side.

FS
OR-G-CA4-B
panel is notched
on top
left side.

FS
OR-G-CA5-B

space between graphic
panels: approx. 4.5″

38.125″ width

43″ width

FS
OR-G-CA1-C

bleed area
trim line

FS
OR-G-CA2-C
panel is notched
on top
right side.

FS
OR-G-CA4-C
panel is notched
on top
left side.

FS
OR-G-CA5-C

FS
OR-G-CA1-D

FS
OR-G-CA2-D
panel is notched
on top
right side.

FS
OR-G-CA4-D
panel is notched
on top
left side.

FS
OR-G-CA5-D

BS

OR-G-CA3-A

– bleed area

– trim line

BS

OR-G-CA3-B

BS

OR-G-CA3-C

BS

OR-G-CA3-D

gray area will
be obstructed
once finished
and mounted

Canis
20’ x 20’ Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE

Panels CA1-A, CA1-B, CA1-C, CA1-D:
Total Graphic Area: 42.125”w x 87.75”h
Finished Size: 38.125”w x 83.75”h

Panels CA2-A, CA2-B, CA2-C, CA2-D:
Total Graphic Area: 47”w x 87.75”h
Finished Size: 43”w x 83.75”h

Panels CA3-A, CA3-B, CA3-C, CA3-D:
Total Graphic Area: 78.75”w x 41.75”h
Finished Size: 74.75”w x 37.75”h

Panels CA4-A, CA4-B, CA4-C, CA4-D:
Total Graphic Area: 42.125”w x 87.75”h
Finished Size: 38.125”w x 83.75”h

Panels CA5-A, CA5-B, CA5-C, CA5-D:
Total Graphic Area: 47”w x 87.75”h
Finished Size: 43”w x 83.75”h

Template requires 1” bleed around the perimeter (2” around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4” w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4”w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location.
Hinging= 3/4” strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

– CMYK Color Mode
– All Solid Coated Pantone colors should be called out in the art as spot colors
– Embed all images and support files
– Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
– All fonts must be created to outlines
– Do not scale artboard
– Background color/images must bleed to the edge of artboard
– Do not use spot colors from template in your artwork as they will not print

FS

OR-G-CA1-A

bleed area
trim line

FS

OR-G-CA2-A

panel is notched
on top
right side.

FS

OR-G-CA4-A

panel is notched
on top
left side.

FS

OR-G-CA5-A

FS

OR-G-CA1-B

FS

OR-G-CA2-B

panel is notched
on top
right side.

FS

OR-G-CA4-B

panel is notched
on top
left side.

FS

OR-G-CA5-B

FS

OR-G-CA1-C

bleed area

trim line

FS

OR-G-CA2-C

panel is notched
on top
right side.

FS

OR-G-CA4-C

panel is notched
on top
left side.

FS

OR-G-CA5-C

FS

OR-G-CA1-D

FS

OR-G-CA2-D

panel is notched
on top
right side.

FS

OR-G-CA4-D

panel is notched
on top
left side.

FS

OR-G-CA5-D