Saturn
10' x 20' Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE
Panels SA1 and SA3:
Total Graphic Area: 77.75"w x 87.75"h
Finished Size: 73.75"w x 83.75"h

Panel SA2:
Total Graphic Area: 51.75"w x 87.75"h
Finished Size: 47.75"w x 83.75"h

Template requires 1" bleed around the perimeter (2" around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4" w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4"w velcro is applied to the front of the panel)
Notching = 7/8" square that is cut into the appropriate location.
Hinging= 3/4" strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-SA1

bleed area
trim line

BS
OR-G-SA2

panel is notched
on all 4 corners

BS
OR-G-SA3

gray area will
be obstructed
once finished
and mounted

Saturn
10’ x 20’ Truss System
Dye Sub Printed



TEMPLATE IS @ 1/2 SCALE
Panels SA1 and SA3:
Total Graphic Area: 77.75”w x 87.75”h
Finished Size: 73.75“w x 83.75”h

Panel SA2:
Total Graphic Area: 51.75”w x 87.75”h
Finished Size: 47.75“w x 83.75”h

Template requires 1” bleed around the perimeter (2” around the perimeter when scaled to 200% and printed)

FS = Graphic is front side mounted (3/4” w velcro is applied to the back of the panel)
BS = Graphic is back side mounted (3/4“w velcro is applied to the front of the panel)
Notching = 7/8” square that is cut into the appropriate location.
Hinging= 3/4” strip of material that is created by notching the graphic. Allows two graphics to share the same extrusion corner.

General Art Guidelines:

- CMYK Color Mode
- All Solid Coated Pantone colors should be called out in the art as spot colors
- Embed all images and support files
- Resolution must be 200-240 ppi @ 1/2 size, 100-120ppi @ 100% size
- All fonts must be created to outlines
- Do not scale artboard
- Background color/images must bleed to the edge of artboard
- Do not use spot colors from template in your artwork as they will not print

BS
OR-G-SA1

bleed area
trim line

BS

OR-G-SA2

panel is notched
on all 4 corners

BS
OR-G-SA3

gray area will
be obstructed
once finished
and mounted